

PAINOAINEISTO-OHJEET

Painoaineiston koko

- Painoaineisto 100% koossa mikäli mahdollista, tarvittaessa skaalaus 50%, 25% tai 10%.

Kuvat ja tekstit

- Seinälevyt ja otsalaudat 150–300ppi, kankaat 72–150ppi.
- Tekstit konverteerituna poluiksi.
- Emme tue Type1-fontteja.
- Suosi logoissa vektoriformaattia (pdf, ai, eps).
- Mikäli materiaali on skaalattu, huomioithan resoluution; esim. 10%:iin skaalatuissa materiaalissa kuvien resoluutioon tulee olla 720ppi, jotta lopullisessa painotuotteessa resoluutio on 72ppi.

Tiedostomuodot

- Toimita valmiit painoaineistot ensisijaisesti PDF-muodossa.
- Käytä PDF-tiedostoissa PDF/X1-a tai Press Quality Print -asetusta.
- Huomioithan mahdollisen materiaalin skaalausvaikutukset PDF-resoluutioasetukseen.
- Kuvatiedostoissa käytämme yleisimpiä tiedostomuotoja, esim. jpg, psd, png tai tif.

Leikkuuvarat ja -merkinnät

- Seinälevyt ja otsalaudat: ei leikkuuvaroja.
- Kankaat: 50mm leikkuuvarat (100% koossa).
- Älä lisää painoaineistoon erikseen leikkuu- tai kohdistusmerkintöjä.

Värimäärittelyt

- Painoaineiston värit oltava aina CMYK-muodossa.
- Käytettävä väripohjali: Coated Fogra39.
- Huom! muissa mahdollisissa värimuodoissa tai -profiileissa toimitetut aineistot muutetaan automaattisesti CMYK-muotoon Fogra39-profilin mukaisesti, jolloin aineiston värit saattavat hieman muuttua.

Aineiston lähettiläminen

- Alle 20Mt aineistot sähköpostilla.
- Yli 20Mt aineistot WeTransfer.com -palvelun kautta.
- Nimeä aineisto seuraavasti: Asiakasrytys_Tapahtuma_Osastonumero_sisältö; esim. YritysX_Verkostomesut 2024_A123_tiskin logolevy.pdf.
- Painovalmis aineisto toimitetaan viimeistään **neljä viikkoa ennen tapahtuman alkua osoitteeseen:**

aineisto.paketit@expotec.fi

PRINTING MATERIAL INSTRUCTIONS

File size

- We prefer 100% file size. Please, use scaling 50%, 25% or 10% only if necessary.

Images and fonts

- Printed wall panels and fascias 150–300ppi, printed fabrics 72–150ppi.
- Fonts must be converted to paths.
- Type1 fonts are not supported.
- Prefer vector format for logos (pdf, ai, eps).
- Please pay special attention to image resolution settings when using scaled material; for example with 10% scaled material you must have 720ppi image resolution to achieve 72ppi in full scale print.

File types

- Deliver print ready materials preferably in PDF format.
- Use PDF/X1-a or Press Quality Print setting when exporting to PDF.
- Please pay special attention to PDF resolution settings when using scaled material.
- Commonly used image formats are accepted, for example jpg, psd, png or tif.

Bleeds and printing marks

- Wall panels and fascias: no bleeds.
- Fabrics: 50mm bleeds (100% size).
- No bleed marks nor trim marks.

Colour definitions

- All colours should be defined as process colours (CMYK).
- Colour profile: Coated Fogra39.
- Please note that materials with any other colour profile are automatically converted to CMYK with Fogra39 profile, which may cause some changes in print colours.

Transferring files

- Smaller than 20MB files by email.
- Over 20MB files via WeTransfer.com service.
- Please, name files as following: Company name_Event_Stand number_content; for example CompanyX_Verkosto 2024_A123_desk logo panel.pdf.
- Please transfer your print-ready files **at least four weeks before the event to the following e-mail address:**

aineisto.paketit@expotec.fi